





Rec'd PCT/PTC

11 APR 2005

IB03/04428



INVESTOR IN PEOPLE



The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ


#2

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated

28 July 2003

**PRIORITY
DOCUMENT**


SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

The
Patent
Office

1/77

Request for grant of a patent

(See notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road
Newport
Gwent NP10 8QQ

1. Your reference	PHGB 020177			18 OCT 2002 0.00-0224277.4
2. Patent application number (The Patent Office will fill in this part)	0224277.4			18 OCT 2002
3. Full name, address and postcode of the or of each applicant (underline all surnames)	KONINKLIJKE PHILIPS ELECTRONICS N.V. GROENEWOUDSEWEG 1 5621 BA EINDHOVEN THE NETHERLANDS			
Patents ADP Number (if you know it)				
If the applicant is a corporate body, give the country/state of its incorporation	THE NETHERLANDS			
4. Title of the invention	ELECTROLUMINESCENT DISPLAY DEVICES			
5. Name of your agent (if you have one)	PAUL LEWIS WILLIAMSON			
"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	Philips Intellectual Property & Standards Cross Oak Lane Redhill Surrey RH1 5HA			
Patents ADP number (if you know it)				
6. If you are declaring priority from one or more earlier patent applications, give the country	Country	Priority Application number	Date of filing	
and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number				
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application		Date of filing (day/month/year)	
8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer "Yes" if:	YES			
a) any applicant named in part 3 is not an inventor, or				
b) there is an inventor who is not named as an applicant, or				
c) any named applicant is a corporate body.				
See note (d))				

07 419 294 001

07 163322082

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document.

Continuation sheets of this form

Description	13
Claims(s)	4
Abstract	1
Drawings	5


10. If you are also filing any of the following, state how many against each item:

Priority Documents

Translations of priority documents
Statement of inventorship and right
to grant of a patent (*Patents Form 7/77*)
Request for preliminary examination and
search (*Patents Form 9/77*)
Request for substantive examination
(*Patents Form 10/77*)
Any other documents
(*Please specify*)

11. I/We request the grant of a patent on the basis of this application.

Signature



Date

17/10/02

12. Name and daytime telephone number of person to contact in the United Kingdom

01293 81 5280

P L WILLIAMSON

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered "Yes" *Patents Form 7/77* will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

DESCRIPTION

ELECTROLUMINESCENT DISPLAY DEVICES

5 This invention relates to electroluminescent display devices, particularly active matrix display devices having thin film switching transistors associated with each pixel.

 Matrix display devices employing electroluminescent, light-emitting, display elements are well known. The display elements may comprise organic
10 thin film electroluminescent elements, for example using polymer materials, or else light emitting diodes (LEDs) using traditional III-V semiconductor compounds. Recent developments in organic electroluminescent materials, particularly polymer materials, have demonstrated their ability to be used practically for video display devices. These materials typically comprise one or
15 more layers of a semiconducting conjugated polymer sandwiched between a pair of electrodes, one of which is transparent and the other of which is of a material suitable for injecting holes or electrons into the polymer layer.

 The polymer material can be fabricated using a CVD process, or simply by a spin coating technique using a solution of a soluble conjugated polymer.
20 Ink-jet printing may also be used. Organic electroluminescent materials exhibit diode-like I-V properties, so that they are capable of providing both a display function and a switching function, and can therefore be used in passive type displays. Alternatively, these materials may be used for active matrix display devices, with each pixel comprising a display element and a switching device
25 for controlling the current through the display element.

 Display devices of this type have current-driven display elements, so that a conventional, analogue drive scheme involves supplying a controllable current to the display element. It is known to provide a current source transistor as part of the pixel configuration, with the gate voltage supplied to
30 the current source transistor determining the current through the display element. A storage capacitor holds the gate voltage after the addressing phase.

Figure 1 shows a known pixel circuit for an active matrix addressed electroluminescent display device. The display device comprises a panel having a row and column matrix array of regularly-spaced pixels, denoted by the blocks 1 and comprising electroluminescent display elements 2 together with associated switching means, located at the intersections between crossing sets of row (selection) and column (data) address conductors 4 and 6. Only a few pixels are shown in the Figure for simplicity. In practice there may be several hundred rows and columns of pixels. The pixels 1 are addressed via the sets of row and column address conductors by a peripheral drive circuit comprising a row, scanning, driver circuit 8 and a column, data, driver circuit 9 connected to the ends of the respective sets of conductors.

The electroluminescent display element 2 comprises an organic light emitting diode, represented here as a diode element (LED) and comprising a pair of electrodes between which one or more active layers of organic electroluminescent material is sandwiched. The display elements of the array are carried together with the associated active matrix circuitry on one side of an insulating support. Either the cathodes or the anodes of the display elements are formed of transparent conductive material. The support is of transparent material such as glass and the electrodes of the display elements 2 closest to the substrate may consist of a transparent conductive material such as ITO so that light generated by the electroluminescent layer is transmitted through these electrodes and the support so as to be visible to a viewer at the other side of the support. Typically, the thickness of the organic electroluminescent material layer is between 100 nm and 200nm. Typical examples of suitable organic electroluminescent materials which can be used for the elements 2 are known and described in EP-A-0 717446. Conjugated polymer materials as described in WO96/36959 can also be used.

Figure 2 shows in simplified schematic form a known pixel and drive circuitry arrangement for providing voltage-programmed operation. Each pixel 1 comprises the EL display element 2 and associated driver circuitry. The driver circuitry has an address transistor 16 which is turned on by a row address pulse on the row conductor 4. When the address transistor 16 is

turned on, a voltage on the column conductor 6 can pass to the remainder of the pixel. In particular, the address transistor 16 supplies the column conductor voltage to a current source 20, which comprises a drive transistor 22 and a storage capacitor 24. The column voltage is provided to the gate of the drive transistor 22, and the gate is held at this voltage by the storage capacitor 24 even after the row address pulse has ended. The drive transistor 22 draws a current from the power supply line 26.

The drive transistor 22 in this circuit is implemented as a PMOS TFT, so that the storage capacitor 24 holds the gate-source voltage fixed. This results in a fixed source-drain current through the transistor, which therefore provides the desired current source operation of the pixel.

The above basic pixel circuit is a voltage-programmed pixel, and there are also current-programmed pixels which sample a drive current. However, all pixel configurations require current to be supplied to each pixel.

One problem with voltage-programmed pixels, particularly using polysilicon thin film transistors, is that different transistor characteristics across the substrate (particularly the threshold voltage) give rise to different relationships between the gate voltage and the source-drain current, and artefacts in the displayed image result. Particularly at low brightness levels, these displays suffer non-uniformity.

Digital drive schemes have also been proposed. In such schemes, the LED device is effectively driven to two possible voltage levels. This overcomes the non-uniformity problem, as the pixels are no longer driven to intermediate low brightness levels. This also reduces the power consumption in the pixel circuit, because a transistor is no longer required to operate in the linear region as a current source. Instead, all transistors can be fully on or fully off, which reduces power consumption. Such a drive scheme is less sensitive to transistor characteristic variations for the same reason. This approach only gives two possible pixel outputs. However, grey scale pixel outputs can be achieved by a number of methods.

In one approach, pixels can be grouped to form larger pixels. Pixels within the group can be addressed independently, so that a grey scale is

produced which is a function of the number of pixels within the group activated. This is known as an area ratio method. A drawback of this approach is the reduced resolution of the display and the increased pixel complexity.

5 In an alternative approach, pixels can be turned on and off more quickly than the frame rate, so that a grey scale is implemented as function of the duty cycle with which the pixel is turned on. This is known as a time ratio method. For example, a frame period may be divided into sub-frame periods in the ratio 1:2:4 (giving 8 evenly spaced grey scale values - i.e. 3 bit resolution). This
10 increases the required driving capability (or else requires a reduction in the frame rate), and therefore increases the cost of the display. Typically, an n -bit grey scale resolution requires n sub-frames. The high refresh rate tends to increase the overall display power consumption, and complicated programming sequences can be required.

15 WO 01/54107 discloses a pixel arrangement and drive scheme for an organic LED display, in which a ramp voltage is applied to the pixel drive transistor. The ramp voltage is shifted in dependence on an input drive level, and the drive transistor switches when the shifted ramp voltage crosses the threshold voltage of the drive transistor.

20

According to the invention, there is provided an active matrix electroluminescent display device comprising an array of display pixels, each pixel comprising:

- an electroluminescent (EL) display element;
 - 25 a drive transistor for driving a current through the display element, a drive voltage being provided to the gate of the drive transistor; and
 - a storage capacitor for storing a drive level and connected between an input to the pixel and the gate of the drive transistor,
- wherein driver circuitry is provided for providing a stepped voltage
30 waveform to the input of the pixel, the stepped voltage waveform being voltage-shifted by the storage capacitor before application to the gate of the drive transistor, and wherein the height of the steps in the stepped voltage

waveform is greater than the voltage width of linear operating region of the drive transistor.

In this arrangement, a stepped signal is provided to the gate of the drive transistor so that one of the steps provides a transition between an on and off state of the drive transistor. The drive voltage dictates when this transition takes place, so that the drive voltage provides a pulse width modulation drive scheme for the drive transistor. By ensuring the height of the steps in the stepped voltage waveform is greater than the range of gate-source voltages in the linear operating region of the drive transistor, it can be ensured that a selected step of the stepped waveform defines a transition for the drive transistor between being fully on and fully off (in either order). In this way, the drive transistor is never driven in the linear region, thereby reducing power consumption.

The height of the steps in the stepped voltage waveform is preferably sufficient to include the linear operating region voltages of the drive transistors of all pixels of the display. In this way, variations in the TFT threshold voltage are overcome, as all pixels are driven to voltages on either side of the linear operating region, even taking into consideration variations in the threshold voltages.

The drive level is thus preferably selected to have one of a plurality of values, and is selected such that any gate voltage for the drive transistor in the linear region corresponds to a voltage between steps of the voltage applied to the gate of the drive transistor. The drive level thus takes into account the range of threshold voltages and the linear regions of the drive transistors so that all pixels are driven either fully on or fully off.

Each pixel preferably further comprises an address transistor, connected between a power supply line and the gate of the drive transistor. This is used to charge the capacitor. Each pixel may further comprise means for disabling the driving of current by the drive transistor through the display element. During the capacitor charging step, the drive transistor can thus be turned off so that it does not influence the capacitor charging step.

The device is thus operable in two modes:

a first mode in which a pixel voltage is applied to the input to the pixel, the address transistor is turned on, the disabling means is turned on to turn off the display element and the storage capacitor is charged to a level derived from the drive voltage; and

5 a second mode in which the address transistor is turned off, the disabling means is turned off and the stepped voltage waveform is applied to the input of the pixel.

These two modes define a programming stage when the input voltage is used to store a voltage on the capacitor, and then a subsequent drive stage.

10 The device may be operable in two sequential phases, one phase providing coarse resolution pulse width modulation and the other, shorter phase, providing fine resolution pulse width modulation. This enables more grey levels to be provided, by having a coarse resolution drive followed (or preceded) by a fine resolution drive.

15 The invention also provides a method of addressing an active matrix electroluminescent display device comprising an array of display pixels, each pixel comprising an electroluminescent (EL) display element, a drive transistor for driving a current through the display element, a drive voltage being provided to the gate of the drive transistor, and a storage capacitor for storing a drive level and connected between an input to the pixel and the gate of the
20 drive transistor, the method comprising, for each pixel:

storing a pixel drive voltage on the storage capacitor;

providing a stepped voltage waveform to the input of the pixel, the stepped voltage waveform being voltage-shifted by the storage capacitor
25 before application to the gate of the drive transistor, such that for a first set of the voltage steps applied to the gate of the drive transistor, the drive transistor is turned on, and for a second set of the voltage steps applied to the gate of the drive transistor, the drive transistor is turned off, the first and second sets being determined by the stored pixel drive level.

30 This method provides time ratio method using a stepped ramped voltage input to the pixel, which is effectively compared with the threshold voltage of the drive transistor. One of the steps provides a voltage which

crosses the threshold voltage of the drive transistor, at which time the transistor is turned on or off, thereby providing control of the transistor duty cycle.

5 The first and second sets of voltage steps may be in either order. Thus, the stepped waveform may ramp up or down, and the point where the gate voltage crosses the transistor threshold voltage may represent the switching on or off of the drive transistor.

10 The height of the steps in the stepped voltage waveform is preferably greater than the voltage width of the linear operating region of the drive transistor, so that the voltages of the steps can be selected so that a step results in the linear operating region of the drive transistor being avoided. In particular, the height of the steps in the stepped voltage waveform can be greater than the voltage width of the overlaid linear operating region voltages of the drive transistors of all pixels of the display, so that the same stepped
15 waveform can be used to avoid the linear operating region of all of the drive transistors.

Thus, the drive level can be selected to have one of a plurality of values, and selected such that any gate voltage for the drive transistor in the linear region corresponds to a voltage between steps of the voltage applied to
20 the gate of the drive transistor.

The device can be operable in two sequential phases, one phase providing coarse resolution pulse width modulation and the other, shorter phase, providing fine resolution pulse width modulation. This enables increased number of levels whilst retaining the required step height to avoid linear driving
25 of the drive transistors.

The invention will now be described by way of example with reference to the accompanying drawings, in which:

Figure 1 shows a known EL display device;

30 Figure 2 is a schematic diagram of a known pixel circuit for current-addressing the EL display pixel using an input drive voltage;

Figure 3 shows a schematic diagram of a pixel layout for a display device of the invention;

Figure 4 is a timing diagram for explaining the operation of the circuit of Figure 3;

5 Figure 5 shows the turn-on characteristics of the drive transistor of the pixel circuit of Figure 3 and is used to explain how the voltage waveforms are selected;

Figure 6 is a timing diagram for explaining a modified operation of the circuit of Figure 3; and

10 Figure 7 is a timing diagram to show how the address operation of the invention is applied to an array of pixels.

The invention provides a pixel layout and drive method for implementing a time ratio drive scheme which uses a stepped reference voltage waveform, the step levels being selected so that the linear operating region of the drive transistor of the pixel is avoided.

The same reference numerals are used in different figures for the same components, and description of these components will not be repeated.

Figure 3 shows a first pixel arrangement in accordance with the invention. As in the conventional pixel of Figure 2, the pixel is voltage-addressed, by applying a gate drive voltage to the drive transistor 22.

20 A storage capacitor 30 is provided between the gate of the drive transistor 22 and the column data line 6. This column data line 6 effectively defines the input to the pixel. The capacitor is provided for voltage-shifting the voltage on the column conductor, as will be explained further below.

25 The column driver circuitry (9 in Figure 1) provides a stepped voltage waveform to the input of the pixel, and this stepped voltage waveform is voltage-shifted by the storage capacitor 30 before application to the gate of the drive transistor. The voltage shift introduced by the capacitor 30 determines when the voltage applied to the gate crosses the threshold voltage of the drive transistor 22.

In order to store the desired voltage on the capacitor 30, each pixel has an address transistor 32, connected between the power supply line 26 and the gate of the drive transistor 22. The address transistor 32 is controlled by an address line 33. This is used to charge the capacitor 30 during a pixel programming stage. During this programming stage, the column conductor 6 is held to a drive voltage (lower than the power supply line voltage) so as to charge the capacitor to the desired voltage.

During the programming stage, no current is driven through the display element 2, and the pixel circuit of Figure 3 has an isolating transistor 34 which is turned off by enable line 36 during this stage. The ground connection of the cathode of the display element 2 may alternatively be provided through a switch, which can be switched to open circuit or to the power supply line voltage to turn off the drive transistor 22. This switch would then be common for all display elements. In such a case, the drain of the drive transistor 22 is connected directly to the anode of the display element 2.

As will be explained further below, the height of the steps in the stepped voltage waveform is greater than the range of gate-source voltages in the linear operating region of the drive transistor. This enables one of the steps to provide a transition between an on and off state of the drive transistor, without driving the transistor in the linear operating region. Indeed, the height of the steps in the stepped voltage waveform is greater than the range of gate-source voltages in the linear operating regions of the drive transistor of all pixels of the display. In this way, the effect of variations in the TFT threshold voltages are eliminated, as all pixels are driven to voltages on either side of the linear operating region.

Figure 4 is used to explain in greater detail the operation of the circuit.

The pixel drive scheme starts with the programming phase. Plot 40 shows the voltage on the address line 33. During the programming phase, the address line voltage is switched low in order to turn on the PMOS address transistor 32. The capacitor 30 is then charged through the address transistor 32 to a voltage dependent on the voltage provided on the column 6. Plot 42 shows the voltage provided on the column, and the part 42a of the plot is the

pixel drive level having a step height shown as 46, which determines the voltage stored across the capacitor 30. During the programming phase, the isolating transistor is turned off, and plot 44 shows the voltage on the enable line 36. The low voltage during the programming phase turns off the NMOS
5 isolating transistor 34.

At the end of the programming phase, the address line voltage 40 goes high, to turn off the address transistor 32, and the voltage 46 is stored on the capacitor 30.

The high level of the address voltage needs to be higher the supply
10 voltage, V_{SUPPLY} , when driving the display element, in order to ensure the address transistor 32 remains off (in the reverse as well as forward direction) regardless of the voltage on the gate of the drive transistor 22. As shown in Figure 4, the high address line voltage can be set at the supply voltage V_{SUPPLY} plus the maximum shift voltage 46.

15 The stepped ramped part 42b of the column voltage 42 is then applied to the column 6, and the effect of the capacitor is to shift this to the plot 48, which is the voltage applied to the gate of the drive transistor 22.

The voltage 48 is initially higher than the supply line voltage so that the PMOS drive transistor 22 is turned off. Only when the voltage steps below the
20 supply line voltage by an amount equal to the threshold voltage of the drive transistor 22 does the transistor turn on, as represented by plot 50 which indicates when a current is driven through the display element 2.

It is apparent that the level of the voltage shift 46 determines the duty cycle of the LED current profile, and this voltage shift thus implements a pulse
25 width modulation drive scheme.

The threshold voltages for different transistors in the array will be slightly different. Furthermore, for gate-source voltages close to the threshold voltage, the drive transistors operate in their linear operating region. This is the region between the fully on and fully off drive conditions of the drive
30 transistor 22.

Figure 5 shows schematically the turn on characteristics of the drive transistor when driving the display element load, and plots the gate-source

voltage versus the source drain current. Below a voltage V_L , the transistor is turned OFF. This may for example be the voltage at which the current flowing is 1% of the peak current. Above a voltage V_H , the transistor is turned ON. This may for example be the voltage at which the current flowing is constant, and thereby limited by the load being driven. For example, this voltage may be defined as the voltage above which the current varies by less than 5% (up to the breakdown voltage). The voltage range between V_L and V_H is the linear operating region of the transistor. Other definitions may be used, but the linear operating region is essentially the operating region where the current increases substantially in response to an increase in gate source voltage, whereas when the transistor is turned fully on or off the current is substantially constant.

The exact values of V_L and V_H will vary for different transistors across the substrate. However, this extent of this variation is predictable or measurable, so that the range of voltage values is known. Furthermore, the range of variation is relatively small, for example 10-15%.

Referring back to Figure 4, the steps of the waveform 42 are selected so that the step height is greater than the voltage width of the linear operating region of the drive transistor 22, namely the voltage width between V_L and V_H . This is ensured for all pixels of the display. As shown in Figure 4, the range of voltages "V_{ON} Range" between the minimum value of V_L and the maximum value of V_H are arranged to lie between steps 52 and 54 of the plot 48.

This is achieved by selecting a step height greater than the range between $V_{L(MIN)}$ and $V_{H(MAX)}$ but also by selecting the voltage level 46 to have a number of discrete possible values so that the range V_{ON} Range is always between voltage step transitions.

The required height of the step is 1V to 1.5V for a low-threshold-voltage TFT, although the values will depend on the particular transistor technology used, and may be significantly higher. In the example shown in Figure 4, 8 steps are provided, which can be easily achieved below the gate breakdown voltage of around 16V. Thus, 8 possible PWM levels can be obtained.

Figure 6 shows a scheme for providing more grey levels, but shows only the plots 42, 48 and 50 of Figure 4. The device is operable in two sequential phases. The order of the two phases is not important, but in Figure 6, the first phase 60 provides a most significant PWM output, namely lower resolution (longer) PWM steps, and the second phase 62 provides higher resolution (shorter) PWM steps. This enables more grey levels to be provided, by having a coarse resolution drive followed by a fine resolution drive. In each phase, the linear operating voltage ranges for the drive transistors are arranged to correspond to the transition between steps, as shown.

In order to address an array of display pixels, all capacitors in the array can initially be charged to the desired values. Once the pixel capacitors have been charged, the same column drive signal (the un-shifted stepped waveform) can be used to drive all pixels in a column simultaneously. Furthermore, all columns can also be driven simultaneously.

In Figure 6, the total frame period may be approximately 17ms, derived from a 60Hz frame rate. If 50% of the frame period is available for emission, and the remainder for the programming sequences and for a guard time between sequences, there is approximately 4ms available for each program cycle. The longer display sequence 60 will last around 7ms and the shorter display sequence 62 will last around 1ms. The shortest step duration, for the 8 steps in the shorter display sequence, will therefore last around 0.1ms.

Figure 7 is used to explain one possible timing scheme for addressing an array of pixels. During a programming phase 70, a sequence of the pulses 42a of Figure 4 is applied to each column conductor simultaneously. Figure 7 shows at 72 the Column voltage waveform for one column conductor. The rows are addressed in turn by the address pulses 74, and these address pulses 74 enable a generated level 42a to be used to charge the storage capacitor of an individual pixel.

At the end of the programming phase 70, all pixels of the array have a selected voltage stored on the capacitor. The drive phase 76 involves applying the same column waveform (the un-shifted stepped ramp) to all columns. All pixels are thus driven simultaneously, with an individual column

conductor waveform being used for the addressing of all pixels in a column, and with column conductor waveforms being applied to all columns at the same time.

It is possible to multiplex the signals applied to the columns, so that groups of columns can be programmed in turn, rather than all simultaneously. This is well known technique, and reduces the number of separate signal generation circuits that are required, as the circuitry for generating the programming sequence can then be shared between columns. As the driving of all pixels involves applying the same signal to all columns, there is no need to consider any multiplexing arrangement for this phase 76.

Figure 7 only shows one address sequence (and also shows that the column signal can ramp up instead of down), but it will be understood that the timing explained with reference to Figure 7 can be extended to provide the two-sequence operation of Figure 6.

The column driver has not been described in detail in the above description, but the conventional driver 9 of Figure 1 can be modified in routine manner to enable generation of the required stepped waveform and the initial pixel programming voltage profile. The required circuitry of the column driver will not be discussed in detail.

In the example above, only one specific pixel layout has been described. It will be understood that different combinations of NMOS and PMOS transistors may be used, and that the pixel circuit may have additional circuit elements to those described for implementing additional functionality, such as in-pixel memory.

The ramped step voltage waveform has been shown with uniform step height and width; but the step height and/or width could be non-uniform without departing from the invention, provided the minimum step height exceeds the determined range of voltages.

Various other modifications will be apparent to those skilled in the art.

CLAIMS

1. An active matrix electroluminescent display device comprising an array of display pixels, each pixel comprising:
 - 5 an electroluminescent (EL) display element;
 - a drive transistor for driving a current through the display element, a drive voltage being provided to the gate of the drive transistor; and
 - a storage capacitor for storing a drive level and connected between an input to the pixel and the gate of the drive transistor,
 - 10 wherein driver circuitry is provided for providing a stepped voltage waveform to the input of the pixel, the stepped voltage waveform being voltage-shifted by the storage capacitor before application to the gate of the drive transistor, and wherein the height of the steps in the stepped voltage waveform is greater than the voltage width of the linear operating region of the
 - 15 drive transistor.
2. A device as claimed in claim 1, wherein the height of the steps in the stepped voltage waveform is sufficient to include the linear operating region voltages of the drive transistors of all pixels of the display.
- 20 3. A device as claimed in claim 1 or 2, wherein the drive level is selected to have one of a plurality of values, and is selected such that any gate voltage for the drive transistor in the linear region corresponds to a voltage between steps of the voltage applied to the gate of the drive transistor.
- 25 4. A device as claimed in any preceding claim, wherein each pixel further comprises an address transistor, connected between a power supply line and the gate of the drive transistor.
- 30 5. A device as claimed in claim 4, wherein each pixel further comprises means for disabling the driving of current by the drive transistor through the display element.

6. A device as claimed in claim 5, wherein the means for disabling comprises an isolating transistor in series with the drive transistor and the display element.

7. A device as claimed in claim 4; wherein the device further comprises disabling means comprising a switch for switching the voltage on one terminal of the display elements of the array of pixels.

8. A device as claimed in claim 5, 6 or 7, wherein the device is operable in two modes:

a first mode in which a pixel voltage is applied to the input to the pixel, the address transistor is turned on, the disabling means is turned on to turn off the display element and the storage capacitor is charged to a level derived from the drive voltage; and

a second mode in which the address transistor is turned off, the disabling means is turned off and the stepped voltage waveform is applied to the input of the pixel.

9. A device as claimed in any preceding claim, wherein the device is operable in at least two sequential phases, one phase providing coarse resolution pulse width modulation and the other, shorter phase, providing fine resolution pulse width modulation.

10. A method of addressing an active matrix electroluminescent display device comprising an array of display pixels, each pixel comprising an electroluminescent (EL) display element, a drive transistor for driving a current through the display element, a drive voltage being provided to the gate of the drive transistor, and a storage capacitor for storing a drive level and connected between an input to the pixel and the gate of the drive transistor, the method comprising, for each pixel:

storing a pixel drive voltage on the storage capacitor;

providing a stepped voltage waveform to the input of the pixel, the stepped voltage waveform being voltage-shifted by the storage capacitor before application to the gate of the drive transistor, such that for a first set of the voltage steps applied to the gate of the drive transistor, the drive transistor
5 is turned on, and for a second set of the voltage steps applied to the gate of the drive transistor, the drive transistor is turned off, the first and second sets being determined by the stored pixel drive level.

11. A method as claimed in claim 10, wherein the height of the steps in the
10 stepped voltage waveform is greater than the voltage width of the linear operating region of the drive transistor.

12. A method as claimed in claim 11, wherein the height of the steps in the stepped voltage waveform is greater than the voltage width of the overlaid
15 linear operating region voltages of the drive transistors of all pixels of the display.

13. A method as claimed in any one of claims 10 to 12, wherein the drive level is selected to have one of a plurality of values, and is selected such that
20 any gate voltage for the drive transistor in the linear region corresponds to a voltage between steps of the voltage applied to the gate of the drive transistor.

14. A method as claimed in any one of claims 10 to 13, wherein the step of storing a pixel drive level on the storage capacitor comprises turning on an
25 address transistor connected between a power supply line and the gate of the drive transistor and charging the storage capacitor using the address transistor.

15. A method as claimed in claim 14, further comprising disabling the
30 driving of current by the drive transistor through the display element during the storing of a pixel drive level on the storage capacitor.

16. A method as claimed in any one of claims 10 to 15, wherein the device is operable in at least two sequential phases, one phase providing coarse resolution pulse width modulation and the other, shorter phase, providing fine resolution pulse width modulation.

5

17. A method as claimed in claim 16, wherein the stepped voltage waveform to the input of the pixel has the same voltage levels in the two phases, and the shorter phase has shorter duration step transitions.


10

ABSTRACT

ELECTROLUMINESCENT DISPLAY DEVICES


5 An active matrix electroluminescent display device uses a stepped voltage waveform to the input of the pixel, the stepped voltage waveform being voltage-shifted by a previously stored pixel drive voltage before application to the gate of a drive transistor. The level of the voltage shift determines the duty cycle with which the display element is driven, and thereby controls the grey level output. The height of the steps in the stepped voltage waveform is greater than the voltage width of linear operating region of the drive transistor, so that a selected step of the stepped waveform defines a transition from the drive transistor between fully on and fully off. In this way, the drive transistor is never driven in the linear region.

15 [Fig. 3]



PRIOR ART

FIG. 1



PRIOR ART

FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7